

according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Product code: OE0003 Revision date: 24.03.2021 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Binding Buffer VG

### Further trade names

Article No. (user):

OE0003

OF00030040

OF00030050

OE00030400

OE00030500

OE00031000

OE00035000

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

specific analysis.

Scientific research and development

## 1.3. Details of the supplier of the safety data sheet

Company name: MolGen B.V. Street: Kazemat 23

Place: NL-3905NR Veenendaal Telephone: +31 (0) 85 - 200 7431

e-mail: info@molgen.com Internet: http://www.molgen.com 1.4. Emergency telephone +31 (0) 85 - 200 7431

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation.

May cause drowsiness or dizziness.

## 2.2. Label elements

## Regulation (EC) No. 1272/2008

## Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol sodium perchlorate, monohydrate

Signal word: Danger

Pictograms:





Telefax: +31 (0) 85 - 200 6901



according to Regulation (EC) No 1907/2006

Binding	Buffer	VG	

Revision date: 24.03.2021 Product code: OE0003 Page 2 of 11

#### Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of waste according to applicable legislation.

#### 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

### **Hazardous components**

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	GHS Classification	GHS Classification				
67-63-0	propan-2-ol; isopropyl	propan-2-ol; isopropyl alcohol; isopropanol				
	200-661-7	603-117-00-0	01-2119457558-25-XXXX			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336					

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Do not leave affected person unattended.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. Get medical advice/attention. If breathing is irregular or stopped, administer artificial respiration.

### After contact with skin

Wash with plenty of water/soap. Immediately remove any contaminated clothing, shoes or stockings. In case of skin reactions, consult a physician.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

## After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Never give anything by mouth to an unconscious person or a person with cramps.



MolGen B.V.

according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Revision date: 24.03.2021 Product code: OE0003 Page 3 of 11

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Respiratory complaints, Unconsciousness, Narcotic effects, Headache.

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder, Nitrogen Co-ordinate fire-fighting measures to the fire surroundings.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Beware of reignition. In case of fire may be liberated: Gases/vapours, toxic

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Evacuate area.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Explosion risk.

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid: Vapour, aerosol or mist formation. Read label before use.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Beware of reignition.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place. Store in a cool dry place. Keep locked up. Store in a place accessible by authorized persons only. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Revision date: 24.03.2021 Product code: OE0003 Page 4 of 11

## Hints on joint storage

Do not store together with: Chlorates, Hydrogen peroxide, Nitrogen oxides (NOx), Alkali metals, Alkaline earth metal, Aluminium, plastic and rubber, Oil, Oxidizing agent. Pyrophoric or self-heating substances, Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

### Further information on storage conditions

Protect against direct sunlight.

## 7.3. Specific end use(s)

specific analysis.

Scientific research and development

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
Worker DNEL, long-term inhalation systemic 500 m				500 mg/m³			
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day			

## **PNEC values**

CAS No	Substance				
Environmental	compartment	Value			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
Freshwater	140,9 mg/l				
Marine water		140,9 mg/l			
Freshwater sediment 552 mg/kg					
Marine sediment		552 mg/kg			
Micro-organisms in sewage treatment plants (STP)		2251 mg/l			
Soil :		28 mg/kg			

### 8.2. Exposure controls









## Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Technical measures and the application of suitable work processes have priority over personal protection equipment.

## Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Avoid:



according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Revision date: 24.03.2021 Product code: OE0003 Page 5 of 11

Vapour, aerosol or mist formation.

### Eye/face protection

Wear eye/face protection.

#### Hand protection

Wear protective gloves. (EN ISO 374)

Suitable material:

NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough time (maximum wearing time): > 480 min

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Respiratory protection necessary at: Vapour, aerosol or mist formation

Filtering device (full mask or mouthpiece) with filter: A (DIN 3181)

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Explosion risk.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: transparent, colourless

Odour: like: Alcohol

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

(Isopropanol) 82 - 83 °C

(Isopropanol) 12 °C

Flammability

Solid: not applicable
Gas: not applicable

**Explosive properties** 

Vapours can form explosive mixtures with air.

Lower explosion limits: (Isopropanol) 2 vol. %
Upper explosion limits: (Isopropanol) 13,4 vol. %
Ignition temperature: (Isopropanol) 425 °C

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined



according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Revision date: 24.03.2021 Product code: OE0003 Page 6 of 11

### **Oxidizing properties**

Not oxidising.

Vapour pressure: not determined

Density: 0.78 g/cm³

Water solubility: miscible

#### Solubility in other solvents

not determined

Partition coefficient:

Viscosity / dynamic:

Not determined

Viscosity / kinematic:

Not determined

Vapour density:

Evaporation rate:

not determined

not determined

#### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Highly flammable.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Reaction with: Alkali metals, Alkaline earth metal, Aluminium

(Ignition hazard. Formation of: Gases/vapours, flammable)

Exothermic reaction with: Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

Explosion hazard with: Chlorates, Hydrogen peroxide, Nitrogen oxides (NOx)

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Protect against direct sunlight.

## 10.5. Incompatible materials

Chlorates, Hydrogen peroxide, Nitrogen oxides (NOx), Alkali metals, Alkaline earth metal, Aluminium, plastic and rubber, Oil, Oxidizing agent. Pyrophoric or self-heating substances, Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

### **Acute toxicity**

Harmful if swallowed.



according to Regulation (EC) No 1907/2006

## **Binding Buffer VG**

Revision date: 24.03.2021 Product code: OE0003 Page 7 of 11

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol							
	oral	LD50 mg/kg	5045	Rat	Manufacturer	RTECS		
	dermal	LD50 mg/kg	12800	Rabbit	Manufacturer	RTECS		
	inhalation (4 h) vapour	LC50	37,5 mg/l	Rat	Manufacturer	OECD 403		

### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

## STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## **Practical experience**

### Other observations

Irritant, Respiratory complaints, Unconsciousness, Narcotic effects, Headache.

Repeated exposure may cause skin dryness or cracking.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

The product is not: Ecotoxic.

The pro	duct is not. Ecotoxic.									
CAS No	Chemical name									
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method					
67-63-0	propan-2-ol; isopropyl alco	propan-2-ol; isopropyl alcohol; isopropanol								
	Acute fish toxicity	LC50 9640 mg/l	96 h Pimephales promelas (fathead minnow)	vendor						

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name							
	Method	Value	d	Source				
	Evaluation	-	-					
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol							
	oxygen depletion	53 %	5					
	biotic/abiotic	95 %	21					

## 12.3. Bioaccumulative potential

The product has not been tested.



according to Regulation (EC) No 1907/2006

	Binding Buffer VG	
Revision date: 24.03.2021	Product code: OE0003	Page 8 of 11

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

## 12.4. Mobility in soil

The product has not been tested.

## 12.5. Results of PBT and vPvB assessment

The product has not been tested.

## 12.6. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

### Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number:** UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code:



according to Regulation (EC) No 1907/2006

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable liquids.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): < 51 %

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):



according to Regulation (EC) No 1907/2006

**Binding Buffer VG** 

Revision date: 24.03.2021 Product code: OE0003 Page 10 of 11

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

### Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible



MolGen B.V.

according to Regulation (EC) No 1907/2006

**Binding Buffer VG** 

Revision date: 24.03.2021 Product code: OE0003 Page 11 of 11

for adhering to existing laws and regulations.