

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wash Buffer II**

Revision date: 24.03.2021

Product code: OE0005

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Wash Buffer II

**Further trade names**

Article No. (user):

OE0005

OE00050060

OE00050080

OE00050600

OE00050800

OE00051000

OE00055000

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

specific analysis.

Scientific research and development

**1.3. Details of the supplier of the safety data sheet**

Company name: MolGen B.V.

Street: Kazemat 23

Place: NL-3905NR Veenendaal

Telephone: +31 (0) 85 - 200 7431

Telefax: +31 (0) 85 - 200 6901

e-mail: info@molgen.com

Internet: http://www.molgen.com

**1.4. Emergency telephone number:**

+31 (0) 85 - 200 7431

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

**2.2. Label elements****Regulation (EC) No. 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 2 of 10

P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of waste according to applicable legislation.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64-17-5	ethanol; ethyl alcohol			70 - < 75 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Do not leave affected person unattended.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest. Get medical advice/attention. If breathing is irregular or stopped, administer artificial respiration.

##### After contact with skin

Wash with plenty of water/soap. Immediately remove any contaminated clothing, shoes or stockings. In case of skin reactions, consult a physician.

##### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Never give anything by mouth to an unconscious person or a person with cramps.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant, Respiratory complaints, Unconsciousness, Narcotic effects, Headache.

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wash Buffer II**

Revision date: 24.03.2021

Product code: OE0005

Page 3 of 10

**Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder, Nitrogen  
Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Beware of reignition. In case of fire may be liberated: Gases/vapours, toxic

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Full protection suit

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Evacuate area.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Explosion risk.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid: Vapour, aerosol or mist formation. Read label before use.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.  
Vapours are heavier than air, spread along floors and form explosive mixtures with air. Beware of reignition.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place. Store in a cool dry place. Keep locked up. Store in a place accessible by authorized persons only. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Chlorates, Hydrogen peroxide, Nitrogen oxides (NO<sub>x</sub>), Alkali metals, Alkaline earth metal, Aluminium, plastic and rubber, Oil, Oxidizing agent. Pyrophoric or self-heating substances, Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

**Further information on storage conditions**

Protect against direct sunlight.

**7.3. Specific end use(s)**

specific analysis.  
Scientific research and development

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 4 of 10

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

##### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol; ethyl alcohol			
Worker DNEL, acute	inhalation	systemic	1900 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>	

##### PNEC values

CAS No	Substance	Value
64-17-5	ethanol; ethyl alcohol	
Freshwater		960 mg/l
Marine water		790 mg/l
Freshwater sediment		3600 mg/l
Micro-organisms in sewage treatment plants (STP)		580000 mg/l
Soil		630 mg/l
Air		2750 mg/l

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Technical measures and the application of suitable work processes have priority over personal protection equipment.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Avoid: Vapour, aerosol or mist formation.

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Wear protective gloves. (EN ISO 374)

Suitable material:

By long-term hand contact:  
NBR (Nitrile rubber)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wash Buffer II**

Revision date: 24.03.2021

Product code: OE0005

Page 5 of 10

Thickness of the glove material: 0,4 mm  
Breakthrough time (maximum wearing time): > 480 min

By short-term hand contact:  
CR (polychloroprene, chloroprene rubber)  
Thickness of the glove material: 0,65 mm  
Breakthrough time (maximum wearing time): > 120 min

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.  
Respiratory protection necessary at: Vapour, aerosol or mist formation  
Filtering device (full mask or mouthpiece) with filter: A (DIN 3181)

**Environmental exposure controls**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Explosion risk.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	transparent, colourless	
Odour:	like: Alcohol	
pH-Value:		not determined

**Changes in the physical state**

Melting point:	not determined
Initial boiling point and boiling range:	(Ethanol) 78 °C
Flash point:	(*) 21 °C

**Flammability**

Solid:	not applicable
Gas:	not applicable

**Explosive properties**

Vapours can form explosive mixtures with air.

Lower explosion limits:	(Ethanol) 3,5 vol. %
Upper explosion limits:	(Ethanol) 15 vol. %
Ignition temperature:	(Ethanol) 425 °C

**Auto-ignition temperature**

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

**Oxidizing properties**

Not oxidising.

Vapour pressure:	not determined
Density:	0,88 g/cm <sup>3</sup>

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 6 of 10

Water solubility: miscible

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Vapour density: not determined

Evaporation rate: not determined

#### 9.2. Other information

(\*) Flash point: 70 Wt % Ethanol in aqueous solution; literature value

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Reaction with: Alkali metals, Alkaline earth metal, Aluminium

(Ignition hazard. Formation of: Gases/vapours, flammable)

Exothermic reaction with: Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

Explosion hazard with: Chlorates, Hydrogen peroxide, Nitrogen oxides (NOx)

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Protect against direct sunlight.

#### 10.5. Incompatible materials

Chlorates, Hydrogen peroxide, Nitrogen oxides (NOx), Alkali metals, Alkaline earth metal, Aluminium, plastic and rubber, Oil, Oxidizing agent. Pyrophoric or self-heating substances, Oxidising agent, Nitric acid, aldehydes, Amines, sulphuric acid, Iron.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 mg/kg	7060	Rat	Manufacturer
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	Manufacturer

##### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 7 of 10

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience

#### Other observations

Irritant, Respiratory complaints, Unconsciousness, Narcotic effects, Headache.

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol; ethyl alcohol					
	Acute fish toxicity	LC50 8140 mg/l	96 h	Leuciscus idus (golden orfe)	Manufacturer	
	Acute crustacea toxicity	EC50 9000 - 14000 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.6. Other adverse effects

No information available.

#### Further information

Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 8 of 10

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 144 601  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 144 601  
Limited quantity: 1 L  
Excepted quantity: E2

### Marine transport (IMDG)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: 144  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 9 of 10

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Warning: flammable liquids.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): < 71 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol; ethyl alcohol

## SECTION 16: Other information

### Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Wash Buffer II

Revision date: 24.03.2021

Product code: OE0005

Page 10 of 10

LD50: Lethal dose, 50%  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road )  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.

### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*